




# SmartCells 6" & 12" Rubber Transition Ramp

6" or 12" rubber transition ramp for SmartCells Flooring, which allows for a zero to 1" or ½" incline, depending on which flooring is selected. Minimizes trip hazards.



- ADA compliant transition ramp options
- Solid rubber construction for durability
- Ideal for doorways or main transition areas
- Available in black or safety yellow



## Product Data

Product	SmartCells Rubber Transition Ramp
Description	12" rubber ramping for use with 1" SmartCells Flooring 6" rubber ramping for use with ½" SmartCells Flooring
Overall Dimensions	12" width by 36" long OR 6" width by 36" long 1" height comprised of two layers of ½" ramp 1" composite height at the thick end tapers down to less than 1/8" "L" lip at top of ramp for simple and full contact on connection
Weight	3 lbs per linear foot
Color	Black or Yellow
Surface Texture	Traction Surface Profile
Add-on Surface Finish	N/A
Composition	Rubber

## Technical Specifications

Durometer Hardness (ASTM D2240)	Shore, type A Durometer: Not less than 55
Flexibility (ASTM D412)	300% modulus: 1400 +/- 300 psi
Tensile Strength (ASTM D412)	1400 psi minimum
Fire Rating	NFPA Flammability Rating: 1

## Chemical Resistance

	SBR	EPDM	Nitrile
Water	Excellent	Excellent	Excellent
Acids	Fair - Good	Fair - Good	Fair - Good
Alkali	Fair	Fair	Fair
Alcohols	Good	Good	Good
Oil & Gasoline	Poor	Poor	Good
Aliphatic/Aromatic Hydrocarbons	Poor	Poor	Good

## Installation:

Ramp placed interlocking with factory edge of SmartCells Flooring (“L” lip on top) and then adhered to subsurface using double-sided tape

## Cleaning:

Sweep or damp mop *(Full cleaning guidelines available upon request)*

## Warranty:

1 Year Limited Warranty *(Full warranty details available upon request)*

For complete information on SmartCells warranty, installation, and cleaning guidelines, please email [info@smartcellsusa.com](mailto:info@smartcellsusa.com) or visit [www.smartcellsusa.com](http://www.smartcellsusa.com)